

NEW LINEA

rivestimento in lamiera d'acciaio verniciata



LP	6,0 kW 9,0 kW	≥ 85,0 %	0,40 - 1,53 kg/h 0,58 - 2,16 kg/h	L47 x P53 x H109 cm	70 *m ² 104 *m ²
LX	9,0 kW 12,0 kW	≥ 85,0 %	0,63 - 2,17 kg/h 0,63 - 2,91 kg/h	L52 x P59,5 x H109 cm	104 *m ² 137 *m ²
LXE	6,0 kW 9,2 kW 12,4 kW	≥ 85,0 %	0,50 - 1,46 kg/h 0,50 - 2,16 kg/h 0,50 - 3,00 kg/h	L52 x P59,5 x H109 cm	70 *m ² 106 *m ² 142 *m ²
LW	7,0 kW 9,0 kW 12,0 kW 15,0 kW 20,0 kW	≥ 90,0 % ≥ 90,0 % ≥ 90,0 % ≥ 90,0 % ≥ 85,0 %	0,50 - 1,56 kg/h 0,50 - 2,17 kg/h 0,50 - 2,77 kg/h 0,73 - 3,45 kg/h 0,83 - 4,76 kg/h	L52 x P59,5 x H109 cm	81 *m ² 104 *m ² 137 *m ² 170 *m ² 180 *m ²
LH	6,0 kW 9,0 kW 12,0 kW	≥ 80,0 % ≥ 80,0 % ≥ 70,0 %	1,76 kg/h 2,70 kg/h 3,60 kg/h	L52 x P60 x H109 cm	70 *m ² 104 *m ² 137 *m ²
LHW	8,0 kW 10,0 kW 12,5 kW 17,5 kW	≥ 80,0 % ≥ 80,0 % ≥ 70,0 % ≥ 76,5 %	2,40 kg/h 2,90 kg/h 4,10 kg/h 5,30 kg/h	L52 x P65 x H109 cm	93 *m ² 115 *m ² 143 *m ² 198 *m ²

* con le condizioni riportate nel catalogo



Rosso



Nero



Grigio metallizzato